

Fast Drying Primer 5lt & 25lt



Fast Drying Primer seals porous substrates and encourages the adhesion of bituminous waterproofing systems and sheet coverings. It may be applied successfully to a wide range of surfaces: Metals - mild steel, zinc, lead. Concrete, Asbestos cement, Slate, Lightweight concrete screeds. The application of the primer varies according to the porosity of the surface: Metal surfaces: 6 - 12m² per litre. Concrete: 6 - 8m² per litre. Lightweight concrete screeds and asbestos cement: 3.5 - 5m² per litre.

All Weather Bitumen Roofing Compound 5lt & 25lt



A solvent-based bituminous compound heavily bodied with fillers and fibres, which is suitable for application by brush or spray. Roofcoat may be applied by brush or by spray. The All Weather Roof coating system may be used on the following surfaces- Asphalt roofs, Built-up felt roofs, Concrete roof decks, Asbestos-Cement sheeting, Metal sheeting, including iron, steel, zinc and lead, Slates, tiles. Roofcoat should normally be applied in 2 coats at 1.0 - 1.5m² per litre per coat, depending upon the porosity of the surface.

Roofing Felt Adhesive & Lap Cement 5lt & 25lt



A solvent based high viscosity bituminous adhesive with strong initial "grab" properties. Felt Adhesive is a cold applied roofing adhesive formulated for convenience and safety, ensuring affinity and a strong, final bond to roofing felts. It is used for bonding all types of roofing felts to metal, timber or concrete, sealing roofing felt laps and bonding chippings to flat roofs. Felt Adhesive is applied at 2 square metres per litre.

Trowel Applied Bitumen Repair Mastic 5lt



Trowelmastic is a plastic, non-slumping compound which provides an effective seal between most roofing materials. It is used for general waterproofing and sealing repairs, cracks, holes and joints either as a finish or before the application of other materials. Uses -filling cracks and fissures in concrete, roofing felt, asphalt, lead, zinc, corrugated asbestos-cement, steel, masonry and renderings. Joint-sealing in gutters, spouts, down-pipes, between corrugated asbestos-cement and iron sheets, around skylights and pre-cast concrete units and bedding tiles, slates and flashings in position.

ROOFING SOLUTIONS



Aluminium Solar Reflective Paint 5lt & 25lt

A solvent-based bituminous aluminium paint, which provides a bright silver finish. Contains a high proportion of quality leafing grade aluminium flake. For the protection against sun and weathering of roofs and walls, particularly where bituminous surfaces, exposed steel and corrugated iron surfaces are encountered. Coverage - Approx. 8.0 m² per litre per coat on smooth surfaces. Approx. 5 - 7m² on porous or rough surfaces.



AQUASHIELD GREY STANDARD – Fibre Reinforced Roof Coating 5kg & 20kg

Aquashield is a high quality solvent based coating with added fibres that interlace to cover up small cracks or gaps to give roofs long term waterproof protection. For use on bituminous surfaces, weathered asphalt, gutters, concrete, brickwork, fibreglass, metal and aged UPVC. Aquashield can be applied to damp surfaces. Aquashield Standard coverage rate is 0.5kg per square metre dependant on substrate.



AQUASHIELD GREY HIGH BUILD – Fibre Reinforced Roof Coating 5kg

Aquashield is a high quality solvent based coating with added fibres that interlace to cover up small cracks or gaps to give roofs long term waterproof protection. For use on bituminous surfaces, weathered asphalt, gutters, concrete, brickwork, fibreglass, metal and aged UPVC. Aquashield can be applied to damp surfaces. Aquashield High Build coverage rate is 1-2kg per square metre dependant on substrate.