

BITUMEN PRODUCTS AND CATIONIC EMULSIONS

CATIONIC GRADE EMULSIONS



K1-40 is a Conventional Grade cationic bitumen emulsion which complies with grade K1-40 of BS 434-1 and grade C40B4 of BS EN 13808. It has been designed as a tack coat for bitumen based surfacing products.

K140% Emulsion 25kg
K140% Emulsion 200kg

K1-60 is a Conventional Grade cationic bitumen emulsion which complies with grade K1-60 of BS 434-1 and grade C60B4 of BS EN 13808. It has been designed as a bond coat for bitumen based surfacing products and as a cold applied surface dressing emulsion.

K160% Emulsion 25kg
K160% Emulsion 200kg

K1-70 is a Conventional Grade cationic bitumen emulsion which complies with grade K1-70 of BS 434-1 and grade C69B3 of BS EN 13808. It has been designed to meet the requirement for a surface dressing emulsion in situations where conventional K1-70 bitumen emulsion will perform satisfactorily.

K170% Emulsion 200kg

Cold Lay Macadam



KEGGED BITUMEN



95/25 Bitumen 45kg Keg
95/25 Bitumen 23kg Bag

50 Pen Bitumen Black 25kg Keg
50 Pen Bitumen Black 20kg Tin
50 Pen Bitumen Red 25kg

OBS 45 Bitumen 20kg

DENSOBAND 10m x 40mm



A polymer modified bitumen strip for sealing joints preventing the ingress of water. Providing a uniform flexible seal, Densoband is ideal for base and wearing course joints that can withstand movement from traffic load and thermal changes.

COLD JOINT PAINT



CJP is an anionic bitumen emulsion formulated for use as a cold applied thixotropic jointing compound as an alternative to hot applied bitumen between vertical faces of asphalt and macadam in compliance with the requirements of BS594-2 and BS 4987-2.